



DHV-tested Equipment

Flying Equipment Database

Manufacturers / Dealers

Fly

DHV Databases

TECHNICAL DATA

DHV TESTREPORT LTF

DHV TESTREPORT EN

DATASHEET

PARTS LIST

OPERATING INSTRUCTION

PRINT

DHV TESTREPORT LTF 2009



SWING ARCUS 7.30

**Type designation** Swing Arcus 7.30  
**Type test reference no** DHV GS-01-1997-12  
**Holder of certification** [Swing Flugsportgeräte GmbH](#)  
**Manufacturer** [Swing Flugsportgeräte GmbH](#)  
**Classification** B  
**Winch towing** Yes  
**Number of seats min / max** 1 / 1  
**Accelerator** Yes  
**Trimmers** No



**BEHAVIOUR AT MIN WEIGHT IN FLIGHT (105KG)**

**BEHAVIOUR AT MAX WEIGHT IN FLIGHT (130KG)**

Test pilots



Harry Buntz



Sebastian Mackrodt

Inflation/take-off

A

A

**Rising behaviour** Smooth, easy and constant rising  
**Special take off technique required** No

Smooth, easy and constant rising  
 No

Landing

A

A

**Special landing technique required** No

No

Speeds in straight flight

A

A

**Trim speed more than 30 km/h** Yes  
**Speed range using the controls larger than 10 km/h** Yes  
**Minimum speed** Less than 25 km/h

Yes  
 Yes  
 Less than 25 km/h

Control movement

A

A

**Symmetric control pressure** Increasing  
**Symmetric control travel** Greater than 65 cm

Increasing  
 Greater than 65 cm

Pitch stability exiting accelerated flight

A

A

**Dive forward angle on exit** Dive forward less than 30°  
**Collapse occurs** No

Dive forward less than 30°  
 No

Pitch stability operating controls during accelerated flight

A

A

**Collapse occurs** No

No


Roll stability and damping

A

A

**Oscillations** Reducing

Reducing

<b>Stability in gentle spirals</b>	<b>A</b>	<b>A</b>
<b>Tendency to return to straight flight</b>	Spontaneous exit	Spontaneous exit
<b>Behaviour in a steeply banked turn</b> 	<b>A</b>	<b>A</b>
<b>Sink rate after two turns</b>	12 m/s to 14 m/s	12 m/s to 14 m/s
<b>Symmetric front collapse</b>	<b>A</b>	<b>A</b>
<b>Entry</b>	Rocking back less than 45°	Rocking back less than 45°
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Change of course</b>	Keeping course	Keeping course
<b>Cascade occurs</b>	No	No
<b>Symmetric front collapse in accelerated flight</b>	<b>A</b>	<b>A</b>
<b>Entry</b>	Rocking back less than 45°	Rocking back less than 45°
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Change of course</b>	Keeping course	Keeping course
<b>Cascade occurs</b>	No	No
<b>Exiting deep stall (parachutal stall)</b>	<b>A</b>	<b>A</b>
<b>Deep stall achieved</b>	Yes	Yes
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Change of course</b>	Changing course less than 45°	Changing course less than 45°
<b>Cascade occurs</b>	No	No
<b>High angle of attack recovery</b>	<b>A</b>	<b>A</b>
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Cascade occurs</b>	No	No
<b>Recovery from a developed full stall</b>	<b>A</b>	<b>A</b>
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Collapse</b>	No collapse	No collapse
<b>Cascade occurs (other than collapses)</b>	No	No
<b>Rocking back</b>	Less than 45°	Less than 45°
<b>Line tension</b>	Most lines tight	Most lines tight
<b>Asymmetric collapse 45-50%</b>	<b>A</b>	<b>A</b>
<b>Change of course until re-inflation</b>	Less than 90°	Less than 90°
<b>Maximum dive forward or roll angle</b>	Dive or roll angle 0° to 15°	Dive or roll angle 0° to 15°
<b>Re-inflation behaviour</b>	Spontaneous re-inflation	Spontaneous re-inflation
<b>Total change of course</b>	Less than 360°	Less than 360°
<b>Collapse on the opposite side occurs</b>	No	No
<b>Twist occurs</b>	No	No
<b>Cascade occurs</b>	No	No
<b>Asymmetric collapse 70-75%</b>	<b>A</b>	<b>A</b>
<b>Change of course until re-inflation</b>	Less than 90°	Less than 90°
<b>Maximum dive forward or roll angle</b>	Dive or roll angle 0° to 15°	Dive or roll angle 0° to 15°
<b>Re-inflation behaviour</b>	Spontaneous re-inflation	Spontaneous re-inflation
<b>Total change of course</b>	Less than 360°	Less than 360°
<b>Collapse on the opposite side occurs</b>	No	No
<b>Twist occurs</b>	No	No
<b>Cascade occurs</b>	No	No
<b>Asymmetric collapse 45-50% in accelerated flight</b>	<b>A</b>	<b>A</b>
<b>Change of course until re-inflation</b>	Less than 90°	Less than 90°
<b>Maximum dive forward or roll angle</b>	Dive or roll angle 0° to 15°	Dive or roll angle 0° to 15°
<b>Re-inflation behaviour</b>	Spontaneous re-inflation	Spontaneous re-inflation
<b>Total change of course</b>	Less than 360°	Less than 360°
<b>Collapse on the opposite side occurs</b>	No	No
<b>Twist occurs</b>	No	No
<b>Cascade occurs</b>	No	No

<b>Asymmetric collapse 70-75% in accelerated flight</b>	<b>B</b>	<b>B</b>
<b>Change of course until re-inflation</b>	90° to 180°	90° to 180°
<b>Maximum dive forward or roll angle</b>	Dive or roll angle 15° to 45°	Dive or roll angle 15° to 45°
<b>Re-inflation behaviour</b>	Spontaneous re-inflation	Spontaneous re-inflation
<b>Total change of course</b>	Less than 360°	Less than 360°
<b>Collapse on the opposite side occurs</b>	No	No
<b>Twist occurs</b>	No	No
<b>Cascade occurs</b>	No	No
<b>Directional control with a maintained asymmetric collapse</b>	<b>A</b>	<b>A</b>
<b>Able to keep course</b>	Yes	Yes
<b>180° turn away from the collapsed side possible in 10 s</b>	Yes	Yes
<b>Amount of control range between turn and stall or spin</b>	More than 50 % of the symmetric control travel	More than 50 % of the symmetric control travel
<b>Trim speed spin tendency</b>	<b>A</b>	<b>A</b>
<b>Spin occurs</b>	No	No
<b>Low speed spin tendency</b>	<b>A</b>	<b>A</b>
<b>Spin occurs</b>	No	No
<b>Recovery from a developed spin</b>	<b>A</b>	<b>A</b>
<b>Spin rotation angle after release</b>	Stops spinning in less than 90°	Stops spinning in less than 90°
<b>Cascade occurs</b>	No	No
<b>B-line stall</b>	<b>A</b>	<b>A</b>
<b>Change of course before release</b>	Changing course less than 45°	Changing course less than 45°
<b>Behaviour before release</b>	Remains stable with straight span	Remains stable with straight span
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 30° to 60°	Dive forward 30° to 60°
<b>Cascade occurs</b>	No	No
<b>Big ears</b>	<b>A</b>	<b>A</b>
<b>Entry procedure</b>	Dedicated controls	Dedicated controls
<b>Behaviour during big ears</b>	Stable flight	Stable flight
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Big ears in accelerated flight</b>	<b>A</b>	<b>A</b>
<b>Entry procedure</b>	Dedicated controls	Dedicated controls
<b>Behaviour during big ears</b>	Stable flight	Stable flight
<b>Recovery</b>	Spontaneous in less than 3 s	Spontaneous in less than 3 s
<b>Dive forward angle on exit</b>	Dive forward 0° to 30°	Dive forward 0° to 30°
<b>Behaviour immediately after releasing the accelerator while maintaining big ears</b>	Stable flight	Stable flight
<b>Behaviour exiting a steep spiral</b>	<b>A</b>	<b>A</b>
<b>Tendency to return to straight flight</b>	Spontaneous exit	Spontaneous exit
<b>Turn angle to recover normal flight</b>	Less than 720°, spontaneous recovery	Less than 720°, spontaneous recovery
<b>Sink rate when evaluating spiral stability [m/s]</b>	14	14
<b>Alternative means of directional control</b>	<b>A</b>	<b>A</b>
<b>180° turn achievable in 20 s</b>	Yes	Yes
<b>Stall or spin occurs</b>	No	No
<b>Any other flight procedure and/or configuration described in the user's manual</b>		

No other flight procedure or configuration described in the user's manual